



Standard cylinder DSNU-16-150-P-A

Part number: 1908265

★ Core product range

FESTO

Based on DIN ISO 6432, for proximity sensing. Various mounting options, with or without additional mounting components. With elastic cushioning rings in the end positions.



Data sheet

| Feature | values |
|--------------------------------------------|-----------------------------------------------------------------------------|
| Stroke | 150 mm |
| Piston diameter | 16 mm |
| Piston rod thread | M6 |
| Cushioning | P: Flexible cushioning rings/plates at both ends |
| Assembly position | Any |
| Conforms to standard | CETOP RP 52 P ISO 6432 |
| Piston-rod end | Male thread |
| Design structure | Piston Piston rod Cylinder barrel |
| Position detection | For proximity sensor |
| Variants | Single-ended piston rod |
| Working pressure | 1 ... 10 bar |
| Mode of operation | double-acting |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 2 |
| Ambient temperature | -20 ... 80 °C |
| Authorization | Germanischer Lloyd |
| Impact energy in end positions | 0.15 J |
| Theoretical force at 6 bar, return stroke | 103.7 N |
| Theoretical force at 6 bar, advance stroke | 120.6 N |
| Moving mass with 0 mm stroke | 23 g |
| Additional weight per 10 mm stroke | 4.6 g |
| Basic weight for 0 mm stroke | 89.9 g |
| Additional mass factor per 10 mm of stroke | 2 g |
| Mounting type | with accessories |
| Pneumatic connection | M5 |
| Materials note | Conforms to RoHS |
| Materials information for cover | Wrought Aluminum alloy neutral anodization |
| Materials information for seals | NBR TPE-U(PU) |
| Materials information for piston rod | High alloy steel, non-corrosive |
| Materials information for cylinder barrel | High alloy steel, non-corrosive |