



# Feed separator HPV-14-20-A

Part number: 529351

FESTO

Integrated SME-8-.../ SMT-8-... sensors. Optimized, accurate adaptation option with ZBH centering sleeves.



## Data sheet

Feature	values
Stroke	20 mm
Piston diameter	14 mm
Max. replacement accuracy	0.3 mm
Max. stem backlash Sx	0.05 mm
Max. stem backlash Sz	0.03 mm
Max. angular gripper jaw backlash ax	0.12 deg
Max. angular gripper jaw backlash ay	0.2 deg
Max. angular gripper jaw backlash az	0.175 deg
Mounting of external fingers	Through-hole
Cushioning	No cushioning
Assembly position	Any
Mode of operation	double-acting
Design structure	twin piston Piston rod Stopper Non-rotating
Position detection	For proximity sensor
Half pulse	111.5 ms
Protection against torque/guide	Square guide
Cycle time	223 ms
Working pressure	3 ... 8 bar
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	2
Ambient temperature	5 ... 60 °C
Max. force on finger Fz static	100 N
Max. torque at gripper finger Mr static	5 Nm
Max. torque at finger Mx static	5 Nm
Max. torque at finger My static	5 Nm
Theoretical force at 6 bar, return stroke	75 N
Theoretical force at 6 bar, advance stroke	90 N
Max. ground per external gripper finger	150 g
Product weight	290 g
alternative connections	M5
Mounting type	Optional Internal thread and centering sleeve With through-hole and centering sleeve
Pneumatic connection	M5
Materials note	Free of copper and PTFE