



Proximity Sensor SME-8-K-24-S6

Part number: 161756

FESTO

Electric, with reed contact, for drives with T-slot, with cable, without LED, heat resistant design.



Data sheet

Feature	values
Design	for T-slot
Conforms to standard	EN 60947-5-2
Materials note	Free of copper and PTFE Conforms to RoHS
Measuring principle	Reed magnetic
Ambient temperature	-40 ... 120 °C
Switch output	with contact, bipolar
Switching element function	Normally open contact
Reproducibility of switching value	+/- 0,1 mm
Switch-on time	≤ 0.5 ms
Switch-off time	≤ 0.03 ms
Max. switching frequency	800 Hz
Max. output current	500 mA
Max. contact rating AC	10 VA
Max. contact rating DC	10 W
Voltage drop	≤ 0 V
Short circuit strength	No
Overload withstand capability	Not available
Operating voltage range AC	0 ... 30 V
Operating voltage range DC	0 ... 30 V
Polarity protected	No
Electrical connection	Cable 2-core
Connector exit direction	axial
Cable length	2.5 m
Materials information, cable sheaths	TPE-S
Mounting type	Clamped in T-slot Insertable into slot lengthwise
Tightening torque	0.2 Nm
Product weight	50 g
Materials information, housing	Epoxy resin PC PET High alloy steel, non-corrosive
Ambient temperature with flexible cable installation	-5 ... 120 °C
Protection class	IP67
Insulation voltage	50 V
Surge strength	0.8 kV
Degree of contamination	3